





| REVISIONS | | |
|-----------|---|---------------|
| REV | DESCRIPTION | APPROVED/DATE |
| A | INCREASED OVERALL LENGTH FROM 8.38 TO 9.24 | 7/17/08 CLB |
| B | REDRAWN FROM SOLID MODEL AND UPDATED HOLE LOCATIONS IN VIEW A-A | 9/22/11 CLB |



VIEW A-A
TYPICAL, BOTH SIDES



| PLY TABLE | | |
|-----------|----------|-------------|
| PLY | MATERIAL | ORIENTATION |
| 101 | NOTE 1 | NONE |
| 102 | NOTE 1 | NONE |
| 103 | NOTE 1 | NONE |
| 104 | NOTE 1 | NONE |
| 105 | NOTE 1 | NONE |

LAYUP PART USING MOLD G12985-MOLD.

FABRICATE IN ACCORDANCE WITH GA001-4 COMPOSITE FABRICATION MANUAL.

MATERIAL: 5 PLYS, 8.7 OZ/YG CROWFOOT BI-DIRECTIONAL E-GLASS, HEXCEL SAFE-T-POXY EPOXY RESIN. 2 COATS (MIN) AD-TECH NO.21 LIGHT GREY COMPOSITE SURFACE FILLER AND FIRE RETARDANT.

OPTIONAL : USE FIRE RESISTANT RESIN CPD 4280A AND HARDENER 4284B. USE OF ADTECH 21 IS OPTIONAL WHEN USING THIS EPOXY AND PPG K36 SURFACE FILLER MAY BE USED INSTEAD.

FINISH: BLACK SATIN ACRYLIC POLYURETHANE.

DIMENSIONS ARE FOR REFERENCE ONLY. PART SHAPE AND GEOMETRY CONTROLLED BY TOOLING

BREAK SHARP EDGES

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

TOLERANCES ARE:

FRACTIONS DECIMAL ANGLES
 $\pm\frac{1}{8}$ $\pm.050$ $\pm 2^\circ$
 $\pm\frac{1}{16}$ $\pm.030$
 $\pm\frac{1}{32}$ $\pm.010$

| | | |
|----------|-----|---------|
| DRAWN | CLB | DATE |
| CHECKED | | 4/15/08 |
| Design | | |
| Approval | CLB | DATE |



THIS DOCUMENT INCLUDES INFORMATION PROPRIETARY
TO GENEVA AVIATION AND SHALL NOT BE USED OR DUPLICATED BY
ANYONE WITHOUT THE WRITTEN PERMISSION OF GENEVA AVIATION, INC.

Drawing Number G12985
Rev B
Pro No: GA129 Size D Scale: NONE Sheet 1 of 1